



**SPECIFICATION:**  
 TRASHSCREEN (TM) SHALL BE AS MANUFACTURED BY:  
 BEST MANAGEMENT PRODUCTS, INC.  
 53 MT. ARCHER RD.  
 LYME CT, 06371  
 800-504-8008  
 WWW.BMPINC.COM

**MATERIAL SHALL BE:**  
 304 NON-MAGNETIC STAINLESS STEEL MIN STD.

STANDARD PERFORATIONS SHALL BE .25" DIAM

INLET AREA SHALL EXCEED INLET AREA FOR SNOOT

TRASHSCREEN SHALL BE SIZED SPECIFICALLY FOR EACH SNOOT SIZE AS PER DIMENSIONS LISTED

TOP OF SCREEN SHALL BE SET AT OUTLET PIPE CENTER LINE

U.S. AND FOREIGN PATENTS PENDING

TRASHSCREEN DIMENSIONS				
SNOUT SIZE	H	W	D	C
18F OR R*	21"	28"	14"	5"
24F OR R*	27"	36"	18"	7"
30FOR R*	32"	46"	23"	8"
36F	45"	50"	25"	9"
48F	57"	68"	34"	11"
52R/72	80"	68"	50"	14"

H= HEIGHT  
 W= WIDTH  
 D= DEPTH  
 C= CLEARANCE FROM BOTTOM OF SCREEN  
 \*R SERIES SNOOTS REQUIRE ADAPTER AT EXTRA COST

<b>BMP, INC.</b>		
53 MT. ARCHER ROAD, LYME, CT. 06371 (800) 504-8008 FAX: (860)434-3195		
DESCRIPTION TRASHSCREEN DIMENSIONS & SPECIFICATION	DATE 7-14-14	SCALE NONE
	DRAWING NUMBER <b>STSDIMSPEC</b>	